

Perl Examples

The long Perl handout has the full explanations -- these are just the notes for the Perl section.

What is Perl?

Free -- open source

Larry Wall

Portable -- no vendor lock-in

Quick-n-dirty

www.cpan.org

Low-road language (Perl) vs. High-road language (Java)

Text processing

Perl Program

Interpreted -- program is a text file

Portable -- Unix, Mac, Windows...

```
#!/usr/bin/perl -w
```

```
print "Hello world!\n";
```

Scalar Variables

Scalar: a number or string

Syntax: start with a \$

Do not need to pre-declare variables

```
$x = 42;
```

```
$y = $x + 13;
```

```
$z = "hello";
```

undef / defined()

Variables are the value **undef** at first, use the `defined()` test

```
if (defined($z)) { ...
```

Strings

Double quotes (") or single quotes (')

```
"Hello\nThere\n" ## string value, with newlines in it
```

```
'Hello' -- Or use single quotes, but then \n's and interpolation are suppressed.
```

Concat with period (.)

```
$str = $z . " twice " . $z; ## concat
```

Interpolation

Variables are evaluated and pasted into a quoted string...

```
$x = 42;
```

```

Sstr = "The answer is $x, so there!\n";      ## the "42" gets pasted in
String comparison
("hello" eq $str) ## case sensitive string equals test
("hello" ne $str) ## case sensitive string not equals test
Do not use the == comparison with strings, == is for numbers
lc(), uc()      ## upper/lower case fns

```

if / while / for

```

()'s required for test
{}'s required for statements -- note: not like C
if
  if (test) { ... }
  if (test) {...} else {...}
  if (test) {...} elsif (test2) { ...}
while
  while(test) {...}
  last -- break out of the loop (like break in C)
  next -- jump to the next iteration (like continue in C)
for loop -- like C

```

Arrays

Features

All purpose array/list type container built in to language (I wish Java had this. It may not be elegant, but it works great.)

Arrays know their length

Can change size dynamically

Can contain different types of elements (strings, ints, ... at the same time)

```

@a = (1, 2);
$x = $a[1];      ## look at the [1] element
$a[0] = 13;     ## change the [0] element
shift / unshift -- operate on "front" or [0] of the array
  shift(@a); ## return and remove [0] element
  unshift(@a, "hello"); ## insert element at front
push / pop -- operate on "end or [len-1] of the array
  pop(@a);
  push(@a, "hello");

```

@ARGV

Special global array, contains the command line arguments

foreach

iterate \$elem over the array (Java needs this too)

```
foreach $elem (@a) {...< code that uses $elem> }
```

Hash Arrays

Like a hash table -- %dict

Use {} to access by key

Assign

```

$dict{"a"} = "aaa";
$dict{"b"} = "bbb";

```

Lookup

```
$dict{"a"}          ## lookup value for key "a"
$dict{"b"}
defined($dict{"z"}) ==> false, since no value for "z"
```

Array Conversion

A hash can be converted to an array of even length with keys in random order

```
@a = %dict;
Now, @a is ("b", "bbb", "a", "bbb")
```

%ENV

Special global hash array, contains the environment vars of our runtime

Subroutines

```
sub() foo {
  my($x, $y) = @_;      ## parameters
  my($z);  ## local var
  return($x + $y);
}
```

```
foo(6, 7) ==> 13
```

@_

@_ is an array of the passed scalar values. Use '=' to make a parallel assignment into local variables (values must be scalars).

Flattening

Cannot pass an array as one of the args -- it all gets "flattened" into @_

my

my() declares something local

Use strict -- \$::global

Refer to outer global vars as \$::global -- needed if the "use strict;" or "use strict 'vars;'" option is on. Use strict is a good idea for a program more than a page or two long.

File Processing

File Handle

Standards: STDIN, STDOUT, STDERR

Custom file handles are by convention all upper-case: FILE, FILE_IN, FILE_OUT

<FILE>

read one line from an input file handle, including the \n

Print to file handle

```
print FILE $x, "hello", $y;      ## write to previously opened FILE
print "Hello there\n";          ## writes to STDOUT by default
```

Write to an output file handle. The things to write are separated by commas, but the file-handle is not. File handle defaults to STDOUT

Open for reading

```
open(IN_FILE, "poem.txt");
```

Open for writing

```
open(OUT_FILE, ">poem2.txt");
```

Standard file processing loop...

```
while ($line = <IN_FILE>) {
  chomp($line); ## remove EOLN
  print $OUT_FILE $line, "\n";
}
```

die -- error detection -- open() returns undef on error

```
open(F, $fname) || die "Cannot open $fname";
```

Regular Expressions

\$str =~ /pattern/

("binky" =~ /ink/) ==> TRUE

("binky" =~ /onk/) ==> FALSE

Match anywhere in string

Do not need to "use up" the whole string

Must use up all of the pattern

Character Codes

Plain characters like 'a', 'X', '9' -- just match exactly

. (a period) -- matches any single character except "\n"

\w -- matches a "word" character: a letter or digit [a-zA-Z0-9]

\W -- (upper-case W) any non word character

\s -- matches a single whitespace character -- space, newline, return, tab, form [\n\r\t\f]

\S -- (upper-case S) any non whitespace character

\t, \n, \d -- tab, newline, decimal digit [0-9]

\ -- inhibit the "specialness" of a character. So, for example, use \. to match a period or \/ to match a slash

/ Variants

"i" after the last / makes it case-insensitive

"m" before the first slash lets you use a delimiter such as "

Examples

"piiig" =~ /p...g/ ==> TRUE . = any char

"piiig" =~ /ii/ ==> TRUE you do not need to use up the whole string

"piiig" =~ /p...g/ ==> FALSE the whole pattern must match

"piiig" =~ /p\w\w\wg/ ==> TRUE \w = any letter or digit

"p123g" =~ /p\d\d\dg/ ==> TRUE \d = 0..9 digit

"piiig" =~ /piIIG/i ==> TRUE "i" makes it case insensitive

"piiig" =~ m"piiig" ==> TRUE "m" allows a delimiter other than /

Control Codes

* -- 0 or more occurrences of the pattern to its left

+ -- 1 or more occurrences of the pattern to its left

| -- logical or -- matches either the pattern on its left or right

parenthesis () -- group sequences of patterns

^ -- matches the start of the string

\$ -- matches the end of the string

Leftmost & Largest

First, Perl tries to find the leftmost match for the pattern, and second it tries to use up as much of the string as possible -- i.e. let + and * use up as many characters as possible.

Regular Expression Examples

These are just lifted from the Perl handout.

These examples gradually demonstrate each of the above control codes. Study them carefully -- small details in regular expressions make a big difference. That's what makes them powerful, but it makes them tricky as well...

```
#### Search for the pattern 'iiig' in the string 'p11iig'
"p11iig" =~ m/iiig/ ==> TRUE
```

```
#### The pattern may be anywhere inside the string
"p11iig" =~ m/iii/ ==> TRUE
```

```
#### All of the pattern must match
"p11iig" =~ m/iiii/ ==> FALSE
```

```
#### . = any char but \n
"p11iig" =~ m/...ig/ ==> TRUE
```

```
"p11iig" =~ m/p.i../ ==> TRUE
```

```
#### The last . in the pattern is not matched
"p11iig" =~ m/p.i.../ ==> FALSE
```

```
#### \d = digit [0-9]
"p123g" =~ m/p\d\d\dg/ ==> TRUE
```

```
"p123g" =~ m/p\d\d\d\d/ ==> FALSE
```

```
#### \w = letter or digit
"p123g" =~ m/\w\w\w\w\w/ ==> TRUE
```

```
#### i+ = one or more i's
"p11iig" =~ m/pi+g/ ==> TRUE
```

```
#### matches iii
"p11iig" =~ m/i+/ ==> TRUE
```

```
"p11iig" =~ m/p+i+g+/ ==> TRUE
```

```
"p11iig" =~ m/p+g+/ ==> FALSE
```

```
#### i* = zero or more i's
"p11iig" =~ m/pi*g/ ==> TRUE
```

```
"p11iig" =~ m/p*i*g*/ ==> TRUE
```

```
#### X* can match zero X's
"p11iig" =~ m/pi*X*g/ ==> TRUE
```

```
#### ^ = start, $ = end
"p11iig" =~ m/^pi+g$/ ==> TRUE
```

```

#### i is not at the start
"piiig" =~ m/^i+g$/ ==> FALSE

#### i is not at the end
"piiig" =~ m/^pi+$/ ==> FALSE

"piiig" =~ m/^p.+g$/ ==> TRUE

"piiig" =~ m/^p.+$/ ==> TRUE

"piiig" =~ m/^.+$/ ==> TRUE

#### g is not at the start
"piiig" =~ m/^g.+$/ ==> FALSE

#### Needs at least one char after the g
"piiig" =~ m/g.+/ ==> FALSE

#### Needs at least zero chars after the g
"piiig" =~ m/g.* / ==> TRUE

#### | = left or right expression
"cat" =~ m/^(cat|hat)$/ ==> TRUE

"hat" =~ m/^(cat|hat)$/ ==> TRUE

"cathatcatcat" =~ m/^(cat|hat)+$/ ==> TRUE

"cathatcatcat" =~ m/^(c|a|t|h)+$/ ==> TRUE

"cathatcatcat" =~ m/^(c|a|t)+$/ ==> FALSE

#### Matches and stops at first 'cat'; does not get to 'catcat' on the right
"cathatcatcat" =~ m/(c|a|t)+/ ==> TRUE

#### ? = optional
"12121x2121x2" =~ m/^(1x?2)+$/ ==> TRUE

"aaaxbbbabaxbb" =~ m/^(a+x?b)+$/ ==> TRUE

"aaaxbbb" =~ m/^(a+x?b)+$/ ==> FALSE

#### Three words separated by spaces
"Easy      does it" =~ m/^\w+\s+\w+\s+\w+$/ ==> TRUE

#### Just matches "gates@microsoft" -- \w does not match the "."
"bill.gates@microsoft.com" =~ m/\w+@\w+/ ==> TRUE

#### Add the .'s to get the whole thing
"bill.gates@microsoft.com" =~ m/^(\\w|\\.)+@(\\w|\\.)+$/ ==> TRUE

#### words separated by commas and possibly spaces
"Klaatu,  barada,nikto" =~ m/^\w+(,\\s*\w+)*$/ ==> TRUE

```

Character Classes

[aeiou] -- a vowel
 [a-zA-Z0-9] -- a word char
 [\w] -- same as above
 [^aeiou] -- anything but a vowel
 /([\w_\.~]+)@([\w_\.~]+)/ -- match an email addr

Special \$X Match Variables

```
if ($str =~ m/(\w+)\s+(\w+)/) {...}
If the if statement is true...
$1 == chars from first ()
$2 == chars from second ()
Use to extract things from the string
` (back-quote) -- before the match
$& -- the match
$' -- after the match
```

Special Example

```
Extract email addr
while ($str =~ /([\w_\.~]+)\@([\w_\.~]+)/) { ## look for an email addr
  print "user:$2 host:$3 all:$1\n";      ## parts of the addr
  $str = $';      ## set the str to be the "rest" of the string
}
```

? Trick

```
Flawed way
m/{(.*)}/ -- pick up all the characters between {}'s -- goes too far
Old, doofy ^ way
m/{([^\^]*)}/ ## the inner [^\^] matches any char except }
New, hip ? way
m/{(.*?)}/ ## pick up all the characters between {}'s, but stop
## at the first }
```

Substitution

```
Change all "is" strings to "is not" -- a sure way to improve any document
$str =~ s/is/is not/ig;
"i" == not case sensitive
"g" == do repeatedly
```